

SAFETY DATA SHEETS

According to the UN GHS revision 9

Version: 1.0
Creation Date: July 15, 2019
Revision Date: July 15, 2019

SECTION 1: Identification

1.1 GHS Product identifier

Product name Mesitylene

1.2 Other means of identification

Product number -
Other names 2,4,6-Me₃-Ph; 2,4,6-trimethylbenzene; 3,5-Dimethyltoluene

1.3 Recommended use of the chemical and restrictions on use

Identified uses Industrial and scientific research use.
Uses advised against no data available

1.4 Supplier's details

Company Shanghai Yansheng Internet Technology Co., Ltd
Address 513, A3 / F, green space future center, Fengxian District, Shanghai, 201400, China
Telephone +86-4000-6969-66

1.5 Emergency phone number

Emergency phone number +86-4000-6969-66
Service hours Monday to Friday, 9am-5pm (Standard time zone: UTC/GMT +8 hours).

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

Flammable liquids, Category 3
Specific target organ toxicity – single exposure, Category 3
Hazardous to the aquatic environment, long-term (Chronic) - Category Chronic 2

2.2 GHS label elements, including precautionary statements

Pictogram(s)



Signal word Warning
Hazard statement(s) H226 Flammable liquid and vapour
H335 May cause respiratory irritation
H411 Toxic to aquatic life with long lasting effects

Precautionary statement(s)

Prevention P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.

Response	P240 Ground and bond container and receiving equipment. P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
	P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment.
Storage	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower]. P370+P378 In case of fire: Use ... to extinguish.
	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P319 Get medical help if you feel unwell. P391 Collect spillage.
Disposal	P403+P235 Store in a well-ventilated place. Keep cool. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

2.3 Other hazards which do not result in classification

no data available

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name	Common names and synonyms	CAS number	EC number	Concentration
Mesitylene	Mesitylene	108-67-8	203-604-4	100%

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

If inhaled

Fresh air, rest. Refer for medical attention.

Following skin contact

Remove contaminated clothes. Rinse skin with plenty of water or shower.

Following eye contact

First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.

Following ingestion

Rinse mouth. Do NOT induce vomiting. Refer for medical attention .

4.2 Most important symptoms/effects, acute and delayed

Excerpt from ERG Guide 129 [Flammable Liquids (Water-Miscible / Noxious)]: May cause toxic effects if inhaled or absorbed through skin. Inhalation or contact with material may irritate or burn skin and eyes. Fire will produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Runoff from fire control or dilution water may cause pollution. (ERG, 2016)

4.3 Indication of immediate medical attention and special treatment needed, if necessary

Immediate first aid: Ensure that adequate decontamination has been carried out. If patient is not breathing, start artificial respiration, preferably with a demand-valve resuscitator, bag-valve-mask device, or pocket mask, as trained. Perform CPR as necessary. Immediately flush contaminated eyes with gently flowing water. Do not induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration. Keep patient quiet and maintain normal body temperature. Obtain medical attention. Aromatic hydrocarbons and related compounds

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

This chemical is a flammable liquid. Poisonous gases are produced in fire. Small fires: dry chemical, carbon dioxide, water spray, or alcohol foam. Large fires: water spray, fog, or alcohol foam. Move container from fire if you can do so without risk. Spray cooling water on containers that are exposed to flames until well after fire is out. For massive fire in cargo area, use unmanned hose holder or monitoring nozzles; if this is impossible, withdraw from area and let fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire. Isolate for one-half mile in all directions if tank car or truck is involved in fire. Vapors are heavier than air and will collect in low areas. Vapors may travel long distances to ignition sources and flashback. Vapors in confined areas may explode when exposed to fire. Containers may explode in fire. Storage containers and parts of containers may rocket great distances, in many directions. If material or contaminated runoff enters waterways, notify downstream users of potentially contaminated waters. Notify local health and fire officials and pollution control agencies. From a secure, explosion-proof location, use water spray to cool exposed containers. If cooling streams are ineffective (venting sound increases in volume and pitch, tank discolors, or shows any signs of deforming), withdraw immediately to a secure position. If employees are expected to fight fires, they must be trained and equipped in OSHA 1910.156.

5.2 Specific hazards arising from the chemical

Excerpt from ERG Guide 129 [Flammable Liquids (Water-Miscible / Noxious)]: HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a (P) may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water. (ERG, 2016)

5.3 Special protective actions for fire-fighters

Use alcohol-resistant foam, dry powder, carbon dioxide. In case of fire: keep drums, etc., cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance. Do NOT wash away into sewer. Do NOT let this chemical enter the environment. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid in sand or inert absorbent. Then store and dispose of according to local regulations.

6.2 Environmental precautions

Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance. Do NOT wash away into sewer. Do NOT let this chemical enter the environment. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid in sand or inert absorbent. Then store and dispose of according to local regulations.

6.3 Methods and materials for containment and cleaning up

Evacuate and restrict persons not wearing protective equipment from area of spill or leak until cleanup is complete. Remove all ignition sources. Ventilate area of spill or leak.

Absorb liquids in vermiculite, dry sand, earth, peat, carbon, or similar material and deposit in sealed containers. Keep this chemical out of a confined space ... because of the possibility of an explosion ... It may be necessary to contain and dispose of this chemical as a hazardous waste. If material or contaminated runoff enters waterways, notify downstream users of potentially contaminated waters. Contact your Department of Environmental Protection or your regional office of the federal EPA for specific recommendations. If employees are required to clean up spills, they must be properly trained and equipped. OSHA 1910.120(q) may be applicable.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

NO open flames, NO sparks and NO smoking. Above 50°C use a closed system, ventilation and explosion-proof electrical equipment. Prevent build-up of electrostatic charges (e.g., by grounding). Handling in a well ventilated place. Wear suitable protective clothing. Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Use non-sparking tools. Prevent fire caused by electrostatic discharge steam.

7.2 Conditions for safe storage, including any incompatibilities

Fireproof. Separated from strong oxidants. Well closed. Keep in a well-ventilated room. Prior to working with this chemical you should be trained on its proper handling and storage. This chemical must be stored to avoid contact with oxidizers (such as perchlorates, peroxides, permanganates, chlorates, and nitrates), and strong oxidizers (such as chlorine, bromine, and fluorine) since violent reactions occur. Store in tightly closed containers in a cool, well-ventilated area away from heat. Sources of ignition such as smoking and open flames are prohibited where this chemical is used, handled, or stored in a manner that could create a potential fire or explosion hazard. Metal containers involving the transfer of 5 gallons or more of this chemical should be grounded and bonded. Drums must be equipped with self-closing valves, pressure vacuum bungs, and flame arresters. Use only nonsparking tools and equipment, especially when opening and closing containers of this chemical.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure limit values

EU-OEL: 100 mg/m³, 20 ppm as TWA. MAK: 100 mg/m³, 20 ppm; peak limitation category: II(2); pregnancy risk group: C

Biological limit values

no data available

8.2 Appropriate engineering controls

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the risk-elimination area.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Wear safety spectacles.

Skin protection

Protective gloves.

Respiratory protection

Use ventilation, local exhaust or breathing protection.

Thermal hazards

no data available

SECTION 9: Physical and chemical properties and safety characteristics

Physical state	1,3,5-trimethylbenzene is a colorless liquid with a peculiar odor. Insoluble in water and less dense than water. Flash point near 123°F. May be toxic by ingestion and inhalation. Used to make plastics and dyes.
Colour	Clear, colorless liquid
Odour	Peculiar odor
Melting point/freezing point	27°C(lit.)
Boiling point or initial boiling point and boiling range	164°C
Flammability	Class II Flammable Liquid
Lower and upper explosion limit/flammability limit	no data available
Flash point	50°C(lit.)
Auto-ignition temperature	1039 deg F (559 deg C)
Decomposition temperature	no data available
pH	no data available
Kinematic viscosity	no data available
Solubility	0.002 % (NIOSH, 2016)
Partition coefficient n-octanol/water	log Kow = 3.42
Vapour pressure	14 mm Hg (55 °C)
Density and/or relative density	0.864
Relative vapour density	4.1 (vs air)
Particle characteristics	no data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Decomposes on burning. This produces toxic and irritating fumes. Reacts violently with strong oxidants. This generates fire and explosion hazard.

10.2 Chemical stability

no data available

10.3 Possibility of hazardous reactions

MODERATE, VIA HEAT, FLAMES, OXIDIZERSTRIMETHYLBENZENE is incompatible with the following: Oxidizers, nitric acid (NIOSH, 2016).

10.4 Conditions to avoid

no data available

10.5 Incompatible materials

Forms explosive mixture with air. Strong oxidizers cause fire and explosion hazard. Violent reaction with nitric acid.

10.6 Hazardous decomposition products

The substance decomposes on burning producing toxic and irritating fumes.

SECTION 11: Toxicological information

Acute toxicity

- Oral: no data available
- Inhalation: no data available
- Dermal: no data available

Skin corrosion/irritation

no data available

Serious eye damage/irritation

no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

STOT-single exposure

The substance is irritating to the eyes, skin and respiratory tract. If this liquid is swallowed, aspiration into the lungs may result in chemical pneumonitis. The substance may cause effects on the central nervous system.

STOT-repeated exposure

The substance defats the skin, which may cause dryness or cracking. Repeated or prolonged inhalation may cause effects on the lungs. This may result in chronic bronchitis. The substance may have effects on the central nervous system and blood. See Notes.

Aspiration hazard

A harmful contamination of the air will be reached rather slowly on evaporation of this substance at 20°C; on spraying or dispersing, however, much faster.

SECTION 12: Ecological information

12.1 Toxicity

- Toxicity to fish: no data available
- Toxicity to daphnia and other aquatic invertebrates: EC50 Daphnia magna /(Water flea)/ 50 mg/L 24 hr, toxic effect: increased mortality and reduced reproduction rates
- Toxicity to algae: EC50; Species: Scenedesmus subspicatus (Green algae, Log growth phase); Conditions: freshwater, static, 24 deg C, pH 8.0-9.3; Concentration: 25000 ug/L for 48 hr; Effect: decreased population biomass
- Toxicity to microorganisms: no data available

12.2 Persistence and degradability

AEROBIC: Dissolved air flotation effluent from a class B petroleum refinery contained 1,3,5-trimethylbenzene at 43 ng/g; greater than 99% removal was shown following activated sludge treatment(1). 1,3,5-Trimethylbenzene at 100 mg/L was not biodegraded over a 14 day period using an activated sludge inoculum(2). Complete removal of 1,3,5-trimethylbenzene (at 0.035 ug/mL soil extract) from sandy loam soil samples contaminated with jet fuel was reported within 5 days; sterile samples with 1,3,5-trimethylbenzene at 0.035 ug/mL soil extract also showed complete removal of this compound within 5 days, probably by evaporation(3). During a 24 hour time period, 500 mg/L of 1,3,5-trimethylbenzene was toxic to the microbes in 2 out of 3 activated sludge inocula(4). 1,3,5-Trimethylbenzene was not biodegraded over a 7.5 day incubation period using an activated sludge inoculum(4).

12.3 Bioaccumulative potential

BCF values of 23-342 and 42-328 were measured in carp for 1,3,5-trimethylbenzene concentrations of 150 and 15 ug/L, respectively(1). According to a classification scheme(2), BCF values of zero to 30 are low and from 100 to 1,000 are high(SRC).

12.4 Mobility in soil

The Koc of 1,3,5-trimethylbenzene has been measured at a range of 501-1,445(1-4). According to a classification scheme(5), this Koc range suggests that 1,3,5-trimethylbenzene is expected to have low mobility in soil. 1,3,5-Trimethylbenzene was detected in soil leachate samples following the addition of crude oil to the surface of a soil trough filled with sand(6).

12.5 Other adverse effects

no data available

SECTION 13: Disposal considerations

13.1 Disposal methods

Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

SECTION 14: Transport information

14.1 UN Number

ADR/RID: UN2325 (For reference only, please check.)

IMDG: UN2325 (For reference only, please check.)

IATA: UN2325 (For reference only, please check.)

14.2 UN Proper Shipping Name

ADR/RID: 1,3,5-

TRIMETHYLBENZENE (For reference only, please check.)

IMDG: 1,3,5-

TRIMETHYLBENZENE (For reference only, please check.)

IATA: 1,3,5-

TRIMETHYLBENZENE (For reference only, please check.)

14.3 Transport hazard class(es)

ADR/RID: 3 (For reference only, please check.)

IMDG: 3 (For reference only, please check.)

IATA: 3 (For reference only, please check.)

14.4 Packing group, if applicable

ADR/RID: III (For reference only, please check.)

IMDG: III (For reference only, please check.)

IATA: III (For reference only, please check.)

14.5 Environmental hazards

ADR/RID: Yes

IMDG: Yes

IATA: Yes

14.6 Special precautions for user

no data available

14.7 Transport in bulk according to IMO instruments

no data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Chemical name	Common names and synonyms	CAS number	EC number
Mesitylene	Mesitylene	108-67-8	203-604-4
European Inventory of Existing Commercial Chemical Substances (EINECS)			Listed.
EC Inventory			Listed.
United States Toxic Substances Control Act (TSCA) Inventory			Listed.
China Catalog of Hazardous chemicals 2015			Listed.
New Zealand Inventory of Chemicals (NZIoC)			Listed.
Philippines Inventory of Chemicals and Chemical Substances (PICCS)			Listed.
Vietnam National Chemical Inventory			Listed.
Chinese Chemical Inventory of Existing Chemical Substances (China IECSC)			Listed.
Korea Existing Chemicals List (KECL)			Listed.

SECTION 16: Other information

Information on revision

Creation Date July 15, 2019

Revision Date July 15, 2019

Abbreviations and acronyms

- CAS: Chemical Abstracts Service
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- RID: Regulation concerning the International Carriage of Dangerous Goods by Rail
- IMDG: International Maritime Dangerous Goods
- IATA: International Air Transportation Association
- TWA: Time Weighted Average
- STEL: Short term exposure limit
- LC50: Lethal Concentration 50%
- LD50: Lethal Dose 50%
- EC50: Effective Concentration 50%

References

- IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>
- HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>
- IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>
- eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website: http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en
- CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>
- ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>
- ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>
- Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>
- ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

Other Information

Use of alcoholic beverages enhances the harmful effect. Depending on the degree of exposure, periodic medical examination is suggested. See ICSCs 1362, 1389 and 1433.

Any questions regarding this SDS, Please send your inquiry to sds@xixisys.com

Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to

appropriate safety precautions. It does not represent any guarantee of the properties of the product. We as supplier shall not be held liable for any damage resulting from handling or from contact with the above product.