

SAFETY DATA SHEETS

According to the UN GHS revision 9

Version: 1.0
Creation Date: July 15, 2019
Revision Date: July 15, 2019

SECTION 1: Identification

1.1 GHS Product identifier

Product name Dibutyl ether

1.2 Other means of identification

Product number -
Other names anhydrous butyl ether; Dibutyl Ether; Butoxymethyl-dimethyl-amin

1.3 Recommended use of the chemical and restrictions on use

Identified uses Industrial and scientific research use.
Uses advised against no data available

1.4 Supplier's details

Company Shanghai Yansheng Internet Technology Co., Ltd
Address 513, A3 / F, green space future center, Fengxian District, Shanghai, 201400, China
Telephone +86-4000-6969-66

1.5 Emergency phone number

Emergency phone number +86-4000-6969-66
Service hours Monday to Friday, 9am-5pm (Standard time zone: UTC/GMT +8 hours).

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

Flammable liquids, Category 3
Skin irritation, Category 2
Eye irritation, Category 2
Specific target organ toxicity – single exposure, Category 3
Hazardous to the aquatic environment, long-term (Chronic) - Category Chronic 3

2.2 GHS label elements, including precautionary statements

Pictogram(s)



Signal word Warning
Hazard statement(s) H226 Flammable liquid and vapour
H315 Causes skin irritation
H319 Causes serious eye irritation
H335 May cause respiratory irritation

| | |
|-----------------------------------|--|
| | H412 Harmful to aquatic life with long lasting effects |
| Precautionary statement(s) | |
| Prevention | <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 Keep container tightly closed.</p> <p>P240 Ground and bond container and receiving equipment.</p> <p>P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.</p> <p>P242 Use non-sparking tools.</p> <p>P243 Take action to prevent static discharges.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...</p> <p>P264 Wash ... thoroughly after handling.</p> <p>P261 Avoid breathing dust/fume/gas/mist/vapours/spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> |
| Response | <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].</p> <p>P370+P378 In case of fire: Use ... to extinguish.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water/...</p> <p>P321 Specific treatment (see ... on this label).</p> <p>P332+P317 If skin irritation occurs: Get medical help.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P319 Get medical help if you feel unwell.</p> |
| Storage | <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p> |
| Disposal | P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. |

2.3 Other hazards which do not result in classification

no data available

SECTION 3: Composition/information on ingredients

3.1 Substances

| Chemical name | Common names and synonyms | CAS number | EC number | Concentration |
|---------------|---------------------------|------------|-----------|---------------|
| Dibutyl ether | Dibutyl ether | 142-96-1 | 205-575-3 | 100% |

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

If inhaled

Fresh air, rest. Refer for medical attention.

Following skin contact

Remove contaminated clothes. Rinse skin with plenty of water or shower.

Following eye contact

First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.

Following ingestion

Rinse mouth. Do NOT induce vomiting. Refer for medical attention .

4.2 Most important symptoms/effects, acute and delayed

Inhalation causes irritation of nose and throat. Liquid irritates eyes and may irritate skin on prolonged contact. Ingestion causes irritation of mouth and stomach. (USCG, 1999)

4.3 Indication of immediate medical attention and special treatment needed, if necessary

Immediate first aid: Ensure that adequate decontamination has been carried out. If patient is not breathing, start artificial respiration, preferably with a demand-valve resuscitator, bag-valve-mask device, or pocket mask, as trained. Perform CPR as necessary. Immediately flush contaminated eyes with gently flowing water. Do not induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration. Keep patient quiet and maintain normal body temperature. Obtain medical attention. Ethers and related compounds

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Use dry chemical, foam, carbon dioxide or water spray. Water may be ineffective. Use water spray to keep fire-exposed containers cool.

5.2 Specific hazards arising from the chemical

Behavior in Fire: Vapor is heavier than air and may travel a considerable distance to a source of ignition and flash back. (USCG, 1999)

5.3 Special protective actions for fire-fighters

Use foam, powder, carbon dioxide. In case of fire: keep drums, etc., cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance. Do NOT let this chemical enter the environment. Cover the spilled material with foam. Collect leaking liquid in sealable containers. Absorb remaining liquid in sand or inert absorbent. Then store and dispose of according to local regulations.

6.2 Environmental precautions

Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid in sand or inert absorbent. Then store and dispose of according to local regulations.

6.3 Methods and materials for containment and cleaning up

Evacuate and restrict persons not wearing protective equipment from area of spill or leak until cleanup is complete. Remove all ignition sources. Establish forced ventilation to keep levels below explosive limit. Absorb liquids in vermiculite, dry sand, earth, peat, carbon, or similar material and deposit in sealed containers. It may be necessary to contain and dispose of this chemical as a hazardous waste. If material or contaminated runoff enters waterways, notify downstream users of potentially contaminated waters. Contact your Department of Environmental Protection or your regional office of the federal EPA for specific recommendations. If employees are required to clean up spills, they must be properly trained and equipped. OSHA 1910.120(q) may be applicable.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

NO open flames, NO sparks and NO smoking. NO contact with hot surfaces. Above 25°C use a closed system, ventilation and explosion-proof electrical equipment. Prevent build-up

of electrostatic charges (e.g., by grounding). Handling in a well ventilated place. Wear suitable protective clothing. Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Use non-sparking tools. Prevent fire caused by electrostatic discharge steam.

7.2 Conditions for safe storage, including any incompatibilities

Fireproof. Separated from incompatible materials. See Chemical Dangers. Cool. Keep in the dark. Store only if stabilized./DUE TO FIRE HAZARD, ETHERS/ ... SHOULD BE KEPT COOL & CONTAINERS ELECTRICALLY GROUNDED TO AVOID SPARKS . ETHERS

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure limit values

no data available

Biological limit values

no data available

8.2 Appropriate engineering controls

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the risk-elimination area.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Wear safety spectacles.

Skin protection

Protective gloves.

Respiratory protection

Use ventilation, local exhaust or breathing protection.

Thermal hazards

no data available

SECTION 9: Physical and chemical properties and safety characteristics

| | |
|---|---|
| Physical state | N-butyl ether is a clear colorless liquid with an ethereal odor. Flash point below 141°F. Less dense than water and insoluble in water. Vapors heavier than air. Irritates the eyes, nose, throat, and respiratory tract. |
| Colour | Colorless liquid |
| Odour | Mild, ethereal odor |
| Melting point/freezing point | -95°C |
| Boiling point or initial boiling point and boiling range | 142-143°C(lit.) |
| Flammability | Flammable. |
| Lower and upper explosion limit/flammability limit | Lower flammable limit: 1.5% by volume; Upper flammable limit: 7.6% by volume |
| Flash point | 25°C |
| Auto-ignition temperature | 365°F |
| Decomposition temperature | no data available |

| | |
|--|--|
| pH | no data available |
| Kinematic viscosity | 0.0069 poise (20 deg C) |
| Solubility | less than 1 mg/mL at 72.5° F (NTP, 1992) |
| Partition coefficient n-octanol/water | log Kow= 3.21 |
| Vapour pressure | 4.8 mm Hg (20 °C) |
| Density and/or relative density | 0.764g/mL at 25°C(lit.) |
| Relative vapour density | 4.48 (vs air) |
| Particle characteristics | no data available |

SECTION 10: Stability and reactivity

10.1 Reactivity

The substance can form explosive peroxides , especially in anhydrous form. Reacts with oxidants. Reacts violently with nitrogen trichloride.

10.2 Chemical stability

no data available

10.3 Possibility of hazardous reactions

ONLY ELECTRICAL EQUIPMENT OF EXPLOSION-PROOF TYPE (GROUP C CLASSIFICATION) IS PERMITTED TO BE OPERATED IN ETHER AREAS. ETHER SHOULD NOT BE STORED NEAR POWERFUL OXIDIZERS OR IN AREAS OF HIGH FIRE HAZARD. /ETHERS/As a result of flow, agitation, etc., electrostatic charges can be generated. Ethers, such as BUTYL ETHER can act as bases. They form salts with strong acids and addition complexes with Lewis acids. The complex between diethyl ether and boron trifluoride is an example. Ethers may react violently with strong oxidizing agents. In other reactions, which typically involve the breaking of the carbon-oxygen bond, ethers are relatively inert.

10.4 Conditions to avoid

no data available

10.5 Incompatible materials

Forms explosive mixture with air. May accumulate static electrical charges, and may cause ignition of its vapors. Incompatible with strong acids, oxidizers. Contact with air or light may form unstable and explosive peroxides, especially anhydrous form.

10.6 Hazardous decomposition products

When heated to decomposition it emits acrid smoke and fumes.

SECTION 11: Toxicological information

Acute toxicity

- Oral: LD50 Rat oral 7.40 (6.41-8.53) mL/kg from table
- Inhalation: no data available
- Dermal: LD50 Rabbit percutaneous 10.08 (4.41-23.04) mL/kg from table

Skin corrosion/irritation

no data available

Serious eye damage/irritation

no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

STOT-single exposure

The substance is mildly irritating to the eyes and respiratory tract. If swallowed the substance may cause vomiting and could result in aspiration pneumonitis.

STOT-repeated exposure

The substance defats the skin, which may cause dryness or cracking.

Aspiration hazard

No indication can be given about the rate at which a harmful concentration of this substance in the air is reached on evaporation at 20°C.

SECTION 12: Ecological information

12.1 Toxicity

- Toxicity to fish: LC50 Pimephales promelas (fathead minnow) 32.5 mg/L 96 hr flow-through bioassay, wt 0.12 g, water hardness 45.5 mg/L CaCO₃, temp: 25 + or - 1 deg C, pH 7.5, dissolved oxygen greater than 60% of saturation
- Toxicity to daphnia and other aquatic invertebrates: EC50; Species: Daphnia magna (Water flea); Conditions: freshwater, static, pH 8.0; Concentration: 150 mg/L for 24 hr; Effect: behavior, equilibrium
- Toxicity to algae: no data available
- Toxicity to microorganisms: no data available

12.2 Persistence and degradability

AEROBIC: Dibutyl ether achieved 16% of its theoretical BOD in screening tests which utilized acclimated mixed microbial cultures over a 5 day incubation period(1). Many ethers are known to be resistant to biodegradation(2). Dibutyl ether at 100 mg/L reached 3 to 4% of its theoretical BOD in 4 weeks using an activated sludge inoculum at 30 mg/L and the Japanese MITI test(3).

12.3 Bioaccumulative potential

BCFs of 47 to 83 and 30 to 114 were measured for carp exposed to 200 and 20 ug/L of dibutyl ether over the course of a 6 week incubation period(1). According to a classification scheme(2), these BCFs suggest bioconcentration in aquatic organisms is moderate to high, provided the compound is not metabolized by the organism(SRC).

12.4 Mobility in soil

Using a structure estimation method based on molecular connectivity indices(1), the Koc for dibutyl ether can be estimated to be 51(SRC). According to a classification scheme(2), this estimated Koc value suggests that dibutyl ether is expected to have high mobility in soil(SRC).

12.5 Other adverse effects

no data available

SECTION 13: Disposal considerations

13.1 Disposal methods

Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

SECTION 14: Transport information

14.1 UN Number

ADR/RID: UN1149 (For reference only, please check.)

IMDG: UN1149 (For reference only, please check.)

IATA: UN1149 (For reference only, please check.)

14.2 UN Proper Shipping Name

ADR/RID: DIBUTYL ETHERS (For reference only, please check.)

IMDG: DIBUTYL ETHERS (For reference only, please check.)

IATA: DIBUTYL ETHERS (For reference only, please check.)

14.3 Transport hazard class(es)

ADR/RID: 3 (For reference only, please check.)

IMDG: 3 (For reference only, please check.)

IATA: 3 (For reference only, please check.)

14.4 Packing group, if applicable

ADR/RID: III (For reference only, please check.)

IMDG: III (For reference only, please check.)

IATA: III (For reference only, please check.)

14.5 Environmental hazards

ADR/RID: No

IMDG: No

IATA: No

14.6 Special precautions for user

no data available

14.7 Transport in bulk according to IMO instruments

no data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

| Chemical name | Common names and synonyms | CAS number | EC number |
|--|---------------------------|------------|-----------|
| Dibutyl ether | Dibutyl ether | 142-96-1 | 205-575-3 |
| European Inventory of Existing Commercial Chemical Substances (EINECS) | | | Listed. |
| EC Inventory | | | Listed. |
| United States Toxic Substances Control Act (TSCA) Inventory | | | Listed. |
| China Catalog of Hazardous chemicals 2015 | | | Listed. |
| New Zealand Inventory of Chemicals (NZIoC) | | | Listed. |
| Philippines Inventory of Chemicals and Chemical Substances (PICCS) | | | Listed. |
| Vietnam National Chemical Inventory | | | Listed. |
| Chinese Chemical Inventory of Existing Chemical Substances (China IECSC) | | | Listed. |
| Korea Existing Chemicals List (KECL) | | | Listed. |

SECTION 16: Other information

Information on revision

Creation Date July 15, 2019

Revision Date July 15, 2019

Abbreviations and acronyms

- CAS: Chemical Abstracts Service
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- RID: Regulation concerning the International Carriage of Dangerous Goods by Rail
- IMDG: International Maritime Dangerous Goods
- IATA: International Air Transportation Association
- TWA: Time Weighted Average
- STEL: Short term exposure limit
- LC50: Lethal Concentration 50%
- LD50: Lethal Dose 50%
- EC50: Effective Concentration 50%

References

- IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>
- HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>
- IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>
- eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website: http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en
- CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>
- ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>
- ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>
- Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>
- ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

Other Information

An added stabilizer or inhibitor can influence the toxicological properties of this substance, consult an expert. Check for peroxides prior to distillation; eliminate if found.

Any questions regarding this SDS, Please send your inquiry to sds@xixisys.com

Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. We as supplier shall not be held liable for any damage resulting from handling or from contact with the above product.